

# 503/554 SS SF 24" LDH SIGNATURE SERIES

55-Ton Hydraulic Detachable Lowboy Trailer with 24" Loaded Deck Height



Load King Trailers, A Utility One Source Company

Mailing: PO Box 427, Elk Point, SD 57025 | Shipping: 701 East Rose Street, Elk Point, SD 57025 | Main: (888) 264-5522 | Fax: (605) 356-3268 | [www.utility1source.com](http://www.utility1source.com) | [www.loadkingtrailers.com](http://www.loadkingtrailers.com)

Construction: 100 KSI/80 KSI Minimum Yield Steel

Estimated Weight: 21,600# estimated base weight

Gooseneck: 110" & 86" Swing Clearance, Non-Ground Bearing

Detachable Wet Kit Operation w/ Hydraulic Frame Lift

5th Wheel Height: 51"

Gooseneck Length: 12' 9"

Gooseneck Ratchet: Enables Multiple Deck/Ride Height Adjustments

Gooseneck Controls: Located at Rear of Gooseneck on Driver's Side for Easy Access

Hydraulic Self-Lifting Detachable: Able to Lift Above or Below Transport Position (Hydraulic Frame Lift Support)

Hydraulics: Powered From Tractor Source (No Pony)

Gooseneck Lock: Air Operated, Self-Locking Fail Safe System (Positive Lock)

Front Flip Ramps: 30" HD Double Hinged

Deck Length: 26' Clear Level Deck

Deck Width: 102"

Loaded Deck Height: 24" LDH & 8" Loaded Ground Clearance

Deck Beams: Cambered w/ 4 Full depth 16" Beams

Wide Load Package: Gussets Behind Each Outrigger

Upper Flange Reinforcement: Between Outriggers

Deck Cross members: Alternating 10" & 4" Crossmembers on 12" Centers

Lowered Crossmembers: ( Last 8' Between Mainbeams )

Decking: 2" Apitong Full Length of Outer Deck (Center Portion Open)

Chain Slots: 13 Pair in Outer Flange

D-Rings: (6) Bent D-Rings Each Side of Deck

Outriggers: 13 Pair Full Depth Swing Out Removable

Rear Drop: 30° (Radiused)

Rear Bolster: ¾ Height

Wheel boxes: Flush Mount

Suspension: Hendrickson Air-Ride

Axles: (3) 27,500# Capacity Each

Axle Spacing: 54"

Tires: (12) Firestone 255/70R22.5 H Radials

Wheels: 8.25 X 22.5 Hub Piloted Steel Disc Wheels

Brakes: 16.5" x 7" Drum Brakes / Spring Brakes on 2 Axle

Brake Air Drain: External Easy Access

Lights: 3rd Tail Light Pkg. w/ Strobes

DOT Rubber Mounted LED Lights & Sealed Harness

Mud flaps: Rubber Anti-Spray/Anti-Sail

Wide Load: Wide Load Sign Pockets (no sign)

Mid Ship: Safety Mid Ship Turn

